

12

EUROPEAN PATENT APPLICATION

21 Application number: 86114266.9

51 Int. Cl.⁴: **D 06 F 37/26**
B 29 C 45/16

22 Date of filing: 15.10.86

30 Priority: 15.10.85 IT 4574785

43 Date of publication of application:
22.04.87 Bulletin 87/17

84 Designated Contracting States:
AT BE CH DE FR GB IT LI LU NL SE

71 Applicant: **Zanussi Elettrodomestici S.p.A.**
Via Giardini Cattaneo, 3
I-33170 Pordenone-C.P. 147(IT)


72 Inventor: **Cinello, Arturo**
Via Grande, 7
I-33032 Bertolo Udine(IT)

72 Inventor: **Durazzani, Piero**
Via Lazio, 7
I-33080 Porcia Pordenone(IT)

74 Representative: **Patentanwälte Grünecker, Kinkeldey,**
Stockmair & Partner
Maximilianstrasse 58
D-8000 München 22(DE)

54 Method for making a laundering tube for a laundry washing machine and laundering tub thus made.

57 A method for making a plastic laundering tub for a laundry washing machine, in which said tub (5) is adapted to contain a rotatable drum (10) supported by bearings (12,13) mounted in a sleeve (14) passing through a respective end wall (8) of the tub. The method is characterized in that the sleeve (14) is made separately from the tub (5) by injection-moulding of a plastic material having a high resistance against mechanical stresses in two successive moulds (16, 20), and that the sleeve (14) is subsequently placed into a third mould (26) for injection-moulding thereabout another plastic material having a lesser resistance against mechanical stresses than the previous one for thus finishing the tub (5).



1

Description

The present invention relates to a method for making a
laundrying tub of a plastic material for a laundry washing
5 machine, and to a laundrying tub made by such method.

Already known is a plastic laundrying tub for a laundry
washing machine (Italian Utility Model No 162,401), this
tub being integrally formed with a respective end wall
carrying at least two bearings for supporting the shaft
10 of the drum of the machine. The bearings are maintained at
axially spaced positions by a metal sleeve interposed
therebetween. Also known (from European Patent No.0043429)
is a plastic laundrying tub made in one piece as in the
preceding case, an end wall of this tub carrying a metal
15 sleeve formed with seats for the bearings mounting the
shaft of the drum of the laundry washing machine. These
tubs offer the advantage of being economically obtainable
of an inexpensive plastic material in a single injection-
moulding operation.

20

On the other hand it has been found in practical use that
the first type of the tub described above is particularly
critical adjacent the locations of the support bearings
for the drum shaft during rotation of the drum.

25

Under these conditions the bearings are subjected to con-
siderable mechanical stresses tending to progressively
deform the material of the tub adjacent the locations of
the bearings.

30

The tubs of the second type described require the seats for
the bearings in the metal sleeve to be separately and
accurately machined, and the bearings to be force-fitted
into the seats of the sleeve after the latter has been
secured to the respective end wall of the tub. The con-
35 struction and manufacture of this tub is thus obviously
rather complicated.

It would now in fact be possible to eliminate the short-
comings of these solutions and to achieve a durable mount-

1 ing of the bearings in a tub if such tub were completely
made of a plastic material capable of sustaining the
mechanical stresses acting on the bearings.

5 In this case, however, the tub would have to be made of an
excessively expensive material and would therefore be
ineconomical for use in a laundry washing machine.

It is therefore an object of the invention to eliminate the
shortcomings and limitations of known plastic laundering
10 tubs for laundry washing machines by providing a laundering
tub of this type in which the support bearings for the
drum shaft are safely retained, excluding any deformation
of the material of the tub during rotation of the drum.

15 These and other objects are attained by a method for mak-
ing a plastic laundering tub for a laundry washing machine,
said tub being adapted to contain a rotatable drum the
drive shaft of which is supported by at least two axially
spaced bearings positioned in a sleeve passing through a
20 respective end wall of the tub.

According to the invention, this method is characterized
in that the sleeve is obtained separately from the tub,
preferably by injection-moulding in two successive pro-
cessing phases of a plastic material having a high resist-
25 ance against mechanical stresses, namely, a first phase
using a first mould for making a spacer element dimensioned
to maintain the bearings at a suitable axial spacing, and
a second phase in which the spacer element is placed in a
second mould together with the bearings, and the plastic
30 material is injection-moulded about the spacer element
and the bearings for finishing the sleeve, the sleeve
being subsequently placed in a third mould in which the
tub is obtained preferably by injection-moulding about the
sleeve of another plastic material having a lesser resist-
35 ance against mechanical stresses than the previous one.

The characteristics of the invention will become more
clearly evident from the following description, given by

1 way of example with reference to the accompanying drawings,
wherein:

fig. 1 shows an axially sectioned view of a laundering tub
6 according to an embodiment of the invention, and
figs. 2, 3 and 4 show diagrammatical sictional views
representing successive phases of the manufacture
of the tub according to fig. 1.

10 With reference to fig. 1, a laundering tub 5 according to
the invention is substantially made of a plastic material
and comprises a peripheral wall 6 and two opposite end
walls 7 and 8, of which end wall 7 is formed with an access
opening 9.

15 The tub is adapted to contain a rotatable drum 10, and is
mounted in a conventional manner in the housing (not shown)
of a laundry washing machine.

20 Drum 10 is provided with a drive shaft 11 supported by at
least two axially spaced bearings 12 and 13 retained in a
sleeve 14 made of a plastic material and passing through
a hub portion 15 formed in end wall 8 of tub 5. The tub
is made by a manufacturing method involving successive
phases as depicted in figs. 2, 3 and 4.

25 In particular, this method is initially directed to the
manufacture of sleeve 14 separately from tub 5, preferably
by injection-moulding in two successive processing phases
(shown respectively in figs. 2 and 3) of a plastic material
having a high resistance against mechanical stresses, for
30 instance glass-fibre reinforced polyester.

For the first processing phase, use is made of a first
mould 16 (fig. 2) having a female element 17 and a male
element 18 configured to form a spacer element 19 in the
35 shape of a cylindrical sleeve, the function of which to be
explained as the description proceeds.

In the subsequent second processing phase, use is made of

1 a second mould 20 (fig. 3) having a female element 21 and
a male element 22 configured to form the sleeve 14 as
specified above. More particularly, male element 22 of
mould 20 is provided with a lateral cylindrical projection
5 23 adapted to have bearing 12, spacer element 19 and bear-
ing 13 mounted thereon prior to being inserted into female
element 21. After bearing 12, spacer element 19 and bear-
ing 13 have been thus mounted on projection 23, the latter
is inserted into female element 21 into compressive
10 engagement therewith of bearing 13 to thereby define an
annular cavity between the outer surfaces of bearings 12
and 13 and spacer element 19 and the inner wall surface of
female element 21.

15 A subsequently injected plastic material is thus injection-
moulded about bearings 12, 13 and spacer element 19 so as
to form the cylindrical wall 25 of sleeve 14 (fig. 1). At
the end of this operation, sleeve 14 is placed in a third
mould 26 (fig. 4) having a female element 27 and a male
20 element 28 cooperating to define a cavity for injection-
moulding tub 5 by the use of another plastic material
having a lesser resistance against mechanical stresses
than the previous one, for instance polypropylene.

In particular, male element 28 of mould 26 has a lateral
25 cylindrical projection 29 adapted to have sleeve 14
mounted thereon prior to male element 28 being inserted
into female element 27. As male element 28 is subsequently
inserted into female element 27 preparatory to injection-
moulding tub 5, projection 29 maintains sleeve 14 in pos-
30 ition between female element 27 and male element 28
adjacent end wall 8 of tub 5 while additionally preventing
the plastic material subsequently injected into mould 26
from penetrating into the sleeve itself.

85 In the closed state of mould 26, female element 27 and male
element 28 cooperate to define cavities 30, 31 and 32
communicating with one another for injection-moulding
peripheral wall 6, end wall 8 and a peripheral flange for

1 securing end wall 7 to tub 5.

The finished tub is thus made of two different types of plastic material, namely, a more expensive first type
5 having a high resistance against mechanical stresses, only a limited amount of which is employed for injection-moulding the portion supporting the drive shaft of the drum, and a less expensive second type having a lesser resistance against mechanical stresses than the previous one, which
10 is injection-moulded about the plastic material of the first type at a sufficient amount for forming the remainder of the tub. This permits simple injection-moulding techniques to be employed for making a plastic laundering tub provided with a reliable mounting for the drum made of a
15 non-deformable material.

20

25

30

35

1

Zanussi Elettrodomestici S.p.A.
Via Giardini Cattaneo, 3
33170 Pordenone-C.P. 147
Italy

5

A. GRUNECKER DR. rer. jur.
DR. H. KINKELDEY DR. rer. jur.
DR. W. STOCKMAIR DR. rer. jur.
DR. K. SCHUMANN DR. rer. jur.
P. H. JAKOB DR. rer. jur.
DR. G. BEZOLD DR. rer. jur.
W. MEISTER DR. rer. jur.
H. HILGERS DR. rer. jur.
DR. H. MEYER-FLATH DR. rer. jur.
DR. M. BOTT-BODENHAUSEN DR. rer. jur.
DR. U. KINKELDEY DR. rer. jur.

LUDWIGSTRASSE 10, D-8000 MÜNCHEN 22

8000 MÜNCHEN 22
MAXIMILIANSSTRASSE 10

10

EP 3049

15

20 Method for Making a Laundering Tub for a
Laundry Washing machine and Laundering Tub
Thus Made

Patent Claims

25

1. A method for making a plastic laundering tub for a
laundry washing machine, said tub being adapted to contain
a rotatable drum the drive shaft of which is supported by
at least two axially spaced bearings positioned in a sleeve
30 passing through a respective end wall of said tub,
characterized in that said sleeve (14) is obtained separately
from said tub (5), preferably by injection moulding
in two successive processing phases of a plastics material
having a high resistance against mechanical stresses,
95 namely, a first phase using a first mould (16) for making
a spacer element (19) dimensioned to maintain said bearings
(12, 13) at a suitable axial spacing, and a second
phase in which said spacer element (19) is placed in a

1 second mould (20) together with said bearings (12, 13), and
the plastics material is injection-moulded about said
spacer element (19) and said bearings (12, 13) for finish-
ing said sleeve (14), said sleeve (14) being subsequently
5 placed in a third mould (26) in which said tub (5) is
obtained preferably by injection-moulding about said
sleeve (14) of another plastics material having a lesser
resistance against mechanical stresses than the previous
one.

10

2. A method according to claim 1, characterized in that
the male element (22) of said second mould (20) is provided
with a lateral cylindrical projection (23) adapted to have
said bearings (12, 13) positioned thereon with said spacer
15 element (19) therebetween, the female element (21) of said
mould (20) being adapted to compressively engage at least
one of said bearings (13).

3. A method according to claim 1, characterized in that
the male element (28) of said third mould (26) is provided
20 with a lateral cylindrical projection (29) adapted to have
said sleeve (14) mounted thereon between said male element
(28) and the female element (27) of said third mould (26)
at a position corresponding to said end wall (8) of said
tub (5).

25

4. A plastic laundering tub for a laundry washing
machine, obtained by the manufacturing method according
to claims 1 - 3, said tub being adapted to contain a
rotatable drum the drive shaft of which is supported by
30 at least two axially spaced bearings positioned in a
sleeve passing through a respective end wall of said tub,
characterized in that said sleeve (14) is made of a plastic
material having a high resistance against mechanical
stresses, and provided with at least one spacer element
35 (19) interposed between said bearings (12, 13) for main-
taining them at axially spaced positions, and that said
tub (5) is made of another plastic material injection-
moulded about said sleeve (14) and having a lesser

1 resistance against mechanical stresses than the previous
one.

5. A laundering tub according to the preceding claims,
5 substantially as described with reference to the accompanying drawings and for the specified purposes.

10

15

20

25

30

35


$\frac{1}{2}$ 

fig. 1

2/2

0219115
fig. 2




fig. 3





fig. 4



(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 86114266.9

(51) Int. Cl.³: **D 06 F 37/26**
B 29 C 45/16

(22) Date of filing: 15.10.86

(30) Priority: 15.10.85 IT 4574785

(43) Date of publication of application:
22.04.87 Bulletin 87/17

(88) Date of deferred publication of search report: 07.01.88

(84) Designated Contracting States:
AT BE CH DE FR GB IT LI LU NL SE

(71) Applicant: **Zanussi Elettrodomestici S.p.A.**
Via Giardini Cattaneo, 3
I-33170 Pordenone-C.P. 147(IT)

(72) Inventor: **Cinello, Arturo**
Via Grande, 7
I-33032 Bertolo Udine(IT)

(72) Inventor: **Durazzani, Piero**
Via Lazio, 7
I-33080 Porcia Pordenone(IT)

(74) Representative: **Patentanwälte Grünecker, Kinkeldey,**
Stockmair & Partner
Maximilianstrasse 58
D-8000 München 22(DE)

(54) Method for making a laundering tube for a laundry washing machine and laundering tub thus made.

(57) A method for making a plastic laundering tub for a laundry washing machine, in which said tub (5) is adapted to contain a rotatable drum (10) supported by bearings (12, 13) mounted in a sleeve (14) passing through a respective end wall (8) of the tub. The method is characterized in that the sleeve (14) is made separately from the tub (5) by injection-moulding of a plastic material having a high resistance against mechanical stresses in two successive moulds (16, 20), and that the sleeve (14) is subsequently placed into a third mould (26) for injection-moulding thereabout another plastic material having a lesser resistance against mechanical stresses than the previous one for thus finishing the tub (5).




Fig. 1



European Patent
Office

EUROPEAN SEARCH REPORT

0219115

Application number

EP 86 11 4266

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
A	EP-A-0 043 429 (ZANUSSI) * Figure 2; abstract *	1, 4	D 06 F 37/26 B 29 C 45/16
A	FR-A-2 316 062 (SKF) * Figure 1; claims *	1	
A	DE-U-7 320 627 (CORDES) * Figure; claims 1,3 *	4	
A	EP-A-0 127 360 (THORN) * Figure 5; abstract *	4	
A	US-A-4 423 540 (HISHIDA) * Figures; abstract *	1	
A	FR-A-1 544 257 (STERN) * Claims *	1	TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			D 06 F B 29 C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 09-10-1987	Examiner COURRIER, G. L. A.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

EPO Form 1503 (03/82)